



THREE CYLINDER PATTERN PERFORATOR

MAIN

The GWF [Three Cylinder Pattern Perforator](#) offers a cost efficient solution to producing high quality perforated items such as [stamps, coupons, game cards, and tear away direct response envelopes](#).

The unit is designed to perforate both in the web direction and across the web using [litho perforation strips](#). It can also be used to perforate in a variety of custom shapes and sizes. It can be installed after the Chills before the Press folder or before a sheeter.

Standard Features :

- Heavy-duty 3" (76mm) steel side frames
- Two plate cylinders, each single around & quipped with [reel rod lockup](#) system
- One double around impression / blanket cylinder equipped with [reel rod lockup](#) system
- Heavy-duty [precision gear drive](#) for tight tolerances and accurate perf-to-print registration
- 360 degree motorized circumferential register
- Motorized +/- 1/4" (6.35mm) on-the-run sidelay adjustment for accurate print registration
- On-the-run depth of perforation adjustment of up to .017" (.43mm)
- A hardened [exit draw roll](#) with on-the-run adjustable [pneumatic slit/perf assemblies](#) for continuous line perforation, continuous slitting, edge trimming, and scoring
- A [centralized grease manifold](#) that allows the unit's main cylinder bearings, sidelay sleeves, and eccentrics to be lubricated from one central location
- [Dial Indicator](#) for impression adjustment
- Manual adjust compensator for plate to plate registration
- Non-driven bypass idler rolls
- Web-up entry platform
- [Remote control box](#)
- [Plate bender](#)
- CE Conformity
- Integrated DMR Automatic Cut-off Register Control
- Unit mounted press stations (entry & exit)
- Web detection system
- Web severer
- High performance shaftless drive
- VPN Ethernet Connection



Example of Installation of
Pattern Perforator

Optional:

- [Upgrade To Magnetic Plate Cylinder.](#)
- [Crusher roller system](#)
- [Auto-Lube system](#)

Specifications:

- Maximum production speed up to 70,000IPH
- Designed for maximum web width of 965mm
- Paper weight g/m² = 40 – 200


Requirements:

- Electrical = 220VAC, 50HZ, 1PH, 20 KW motor
- High pressure air: 0,0224 m³/min @ 5,5 Bars



Product Applications:

- Stamps
- Coupons
- Game cards
- Business reply cards




Perforator Litho Strips




THREE CYLINDER PATTERN PERFORATOR

◀ MAIN



View Workside



View Inside



**Optional – Universal Semi-Automatic
Plate Bender**



Manual Plate bender – “Bendito”



◀ MAIN



**3493 East 83rd Ave.
Merrillville, IN 46410 USA
Tel: +1-219-942-7000, Fax: +1-219-942-7001
www.gwf.cc**